

X

इंटरनेट



Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

"जानने का अधिकार, जीने का अधिकार" Mazdoor Kisan Shakti Sangathan "The Right to Information, The Right to Live"

 $\star \star \star \star \star \star \star \star$

"पुराने को छोड नये के तरफ" Jawaharlal Nehru "Step Out From the Old to the New"

मानक

IS 1125 (1974): Method of test for determination of weathering of natural building stones [CED 6: Stones]

111/1/201

Made Available By Public.Resource.Org

 $\star \star \star \star \star \star \star$

"ज्ञान से एक नये भारत का निर्माण″ Satyanarayan Gangaram Pitroda "Invent a New India Using Knowledge"

RIGHT TO INFORMATION "ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता Bhartrhari-Nītiśatakam "Knowledge is such a treasure which cannot be stolen"



BLANK PAGE



PROTECTED BY COPYRIGHT

Indian Standard

METHOD OF TEST FOR DETERMINATION OF WEATHERING OF NATURAL BUILDING STONES

(First Revision)

Second Reprint SEPTEMBER 1989

UDC 691.21:620.193.21

@ Copyright 1975

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

March 1975

Gr 2

Indian Standard

METHOD OF TEST FOR DETERMINATION OF WEATHERING OF NATURAL BUILDING STONES

(First Revision)

Stones Sectional Committee, BDC 6

Chairman

Representing

SHRIC. B. L. MATHUR Public Works Department, Government of Rajasthan, Jaipur

Members

STARI K. K. AGRAWALA SHRI K. K. MADHOK (Alternate) SHRI T. N. BHARGAVA CHIEF ABCHITECT LALA G. C. DAS SHRI P. R. DAS (Alternate) DEPUTY DIRECTOR (RESEARCH) Public DEPUTY DIRECTOR (RESEARCH), CONTROL & RESEARCH LABORATORY DR M. P. DHIR Delhi SHRI R. L. NANDA (Alternate) DIRECTOR DIRECTOR (CSMRS) DEPUTY DIRECTOR (CSMRS) (Alternate) DIRECTOR, MERI Ruilding & RESEARCH OFFICER, MERI (Alternate) SHEI M. K. GUPTA SHRI S. D. PATHAK (Alternate) DR IQBAL ALI

SHRI A. B. LINGAM (Alternate)

Builders' Association of India, Bombay

Ministry of Shipping & Transport (Roads Wing) Central Public Works Department, New Delhi National Test House, Calcutta

Public Works Department, Government of Uttar Pradesh, Lucknow

Public Works Department, Government of Orissa, Bhuvaneshwar

Central Road Research Institute (CSIR), New Delhi

Engineering Research Institute, Baroda

Central Water & Power Commission, New Delhi Alternate)

Building & Communication Department, Government of Maharashtra, Bombay

Himalayan Tiles & Marble Pvt Ltd, Bombay

Engineering Research Laboratory, Government of Andhra Pradesh, Hyderabad

(Continued on page 2)

© Copyright 1975 BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)				
Members	Representing			
SHRI D. G. KADRADE SHRI V. B. DESAI (Alternate)	Hindustan Construction Co Ltd, Bombay			
SHRI T. R. MEHANDRU SHRI PREM SWARUP	Institution of Engineers (India), Calcutta Department of Geology & Mining, Government of Uttar Pradesh, Lucknow			
SHRI A. K. AGABWAL (Alternate))			
DR A. V. R. RAO DEPUTY DIRECTOR (MATERIAL	National Buildings Organization, New Delhi 3) (Alternate)			
SHRI M. L. SETHI	Department of Geology and Mining, Government of Rajasthan, Jaipur			
SHEI Y. N. DAVE (Alternate)				
DR B. N. SINHA	Geological Survey of India, Calcutta			
SUPERINTENDING ENGINEER (DESIGNS)	Public Works Department, Government of Mysore, Bangalore			
SUPERINTENDING ENGINEER (DESIGN)	Public Works Department, Government of Tamil Nadu, Madras			
DEPUTY CHIEF ENGINEEB (I & D) (Alternate)				
SUPERINTENDING ENGINEER (DESIGN & PLANNING)	Public Works Department, Government of Andhra Pradesh, Hyderabad			
SUPERINTENDING ENGINEER (PLANNING CIRCLE)	Public Works Department, Government of West Bengal, Calcutta			
SUPERINTENDING SURVEYOR OF	Public Works Department, Government of Himachal Pradesh, Simla			
SHRI M. V. YOGI	Engineer-in-Chief's Branch (Ministry of Defence)			
SHRI J. N. CHARAN (Atternate) SHRI D. AJITHA SIMHA, Director (Civ Engg)	Director General, BIS (Ex-officio Member)			

Secretary

SHRI K. M. MATHUB Deputy Director (Civ Engg), BIS

Indian Standard

METHOD OF TEST FOR DETERMINATION OF WEATHERING OF NATURAL BUILDING STONES

(First Revision)

0. FOREWORD

0.1 This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 8 October 1974, after the draft finalized by the Stones Sectional Committee had been approved by the Civil Engineering Division Council.

0.2 Building stones are available in large quantity in various parts of the country. To choose and utilize them for their satisfactory performance it is necessary to know the various strength properties determined according to standard procedure. This standard has, therefore, been formulated to cover the standard method for determining the weathering of various stones. This standard was first published in 1957 and has been revised based on its actual use in the past 17 years and the experience gained in testing of building stones for this property in the various research laboratories of this country. This test method is prescribed to find out the resistance of stone towards corrosive ground water, wetting and drying, sulphate attack and temperature variations.

0.3 In reporting the results of a test or analysis made in accordance with this standard, if the final value observed or calculated, is to be rounded off, it shall be done in accordance with IS : $2-1960^*$.

1. SCOPE

1.1 This standard lays down the procedure for testing weathering of natural building stones used for constructional purposes.

^{*}Rules for rounding off numerical values (revised).

IS: 1125 - 1974

2. SELECTION OF SAMPLE

2.1. The sample shall be selected to represent a true average of the type or grade of stone under consideration.

2.2 The sample shall be selected from the quarried stone or taken from the natural rock, as described in 2.2.1 and 2.2.2, and shall be of adequate size to permit the preparation of the requisite number of test pieces.

2.2.1 Stones from Ledges or Quarries — The ledge or quarry face of the stone shall be inspected to determine any variation in different strata. Differences in colour, texture and structure shall be observed. Separate samples of stone weighing at least 25 kg each of the unweathered specimens shall be obtained from all strata that appear to vary in colour, texture and structure. Pieces that have been damaged by blasting, driving wedges, heating, etc, shall not be included in the sample.

2.2.2 Field Stone and Boulders — A detailed inspection of the stone and boulders over the area shall be made where the supply is to be obtained. The different kinds of stone and their condition at various quarry sites shall be recorded. Separate samples for each class of stone that would be considered for use in construction as indicated by visual inspection shall be selected.

2.3 When perceptible variations occur in the quality of rock, as many samples as are necessary for determining the range in properties shall be selected.

3. TEST PIECES

3.1 The test pieces shall be either cylinders, 50 mm in diameter and 50 mm in height, or 50 mm cubes.

3.2 The test pieces shall be finished smooth and the edges shall be rounded to a radius of approximately 3 mm by grinding.

3.3 At least three test pieces shall be used for conducting the test.

3.4 The test pieces shall be dried in a well ventilated oven for 24 h at $105 \pm 5^{\circ}$ C and cooled in a desiccator to room temperature (20 to 30°C).

4. APPARATUS

4.1 The apparatus shall be as illustrated in Fig. 1. It shall consist of an enclosed balance of one kilogram capacity that is sensitive to 0.01 g and suitable accessories for weighing the specimen in water.

4



FIG. 1 APPARATUS FOR CONDUCTING WEATHERING TEST

IS: 1125 - 1974

5. PROCEDURE

5.1 The dried and cooled test pieces (see 3.4) shall be weighed to the nearest 0.01 g and the weight of each recorded (W_1). The specimens shall then be submerged in water at 20 to 30°C for 24 hours. Each specimen shall be weighed (W_2) whilst totally immersed and freely suspended in water (when weighing test pieces in water, they shall be weighed suspended in such a position that air is not entrapped in the cavities). It shall then be removed, the surface water wiped off with a damp cloth and weighed again (W_3). The weighing of each specimen shall be completed within three minutes of its removal from water.

5.2 Each specimen shall be placed in a flat dish, made of glass, porcelain or glazed stonework, 9 cm in diameter and 1.5 cm in depth to which shall be added 2 g of powdered gypsum and 25 ml of water. The dishes together with specimens shall then be placed in a well ventilated oven and maintained at a temperature of $105 \pm 2^{\circ}$ C for at least 5 hours or until the water has evaporated and the powder becomes dry. The dishes shall be removed from the oven and cooled to $25 \pm 5^{\circ}$ C. This completes the first cycle. The cycle shall then be repeated 29 times in the same manner, except that only 25 ml of water shall be added for each of the subsequent cycles.

5.3 At the end of the 30 cycles, the specimens shall be cleaned by brushing with a stiff-fibre brush to remove any particles of gypsum clinging to the surface. Each specimen shall be immersed in water for 24 hours, surface dried, and weighed first in air (W_4) and then in water (W_5) as described in 5.1.

6. EVALUATION

6.1 The increase/change in absorption and the increase in volume of each test piece after the 30 cycles of the test shall be calculated as follows:

$A_1 = \frac{W_3 - W_1}{W_1} \times 100$	•••		•••	(1)
--	-----	--	-----	-----

$$V_1 = \frac{W_3 - W_2}{d}$$
 (2)

$$A_2 = \frac{W_4 - W_1}{W_1} \times 100 \qquad \dots \qquad \dots \qquad \dots \qquad (3)$$

Increase in absorption, percent =
$$\frac{A_2 - A_1}{A_1} \times 100$$
 ... (5)

Increase in volume, percent =
$$\frac{V_2 - V_1}{V_1} \times 100$$
 ... (6)

where

- A_1 = original absorption of the specimen during 24-h immersion in water, expressed as percentage by weight;
- $W_3 =$ original weight of surface-dried specimen after 24-h immersion in water (see 5.1);
- $W_1 =$ original weight of the oven-dried specimen before immersion (see 5.1);
- V_1 = original volume of the specimen after 24-h immersion in water;
- $W_2 =$ original weight of specimen freely suspended in water after 24-h immersion (see 5.1);
- d =density of water at the temperature of observation (see 5.1);
- $A_2 =$ final absorption of the specimen after 30 cycles of the test expressed as percentage by weight;
- W_4 = final weight in air of surface-dried specimen after 30 cycles of the test and 24-h immersion in water (see 5.3);
- V_2 = final volume of the specimen after 30 cycles of the test; and
- $W_5 =$ final weight of the specimen freely suspended in water after 30 cycles of the test and 24-h immersion in water (see 5.3).

7. REPORT OF TEST RESULTS

7.1 The average of the three individual determinations shall be reported as the percentage increase in absorption and percentage increase in volume of the sample.

7.2 The following additional information shall be reported along with the test results:

- a) A description of the way in which the test pieces were prepared;
- b) Size and shape of the test pieces used in the tests; and
- c) Identification of the sample, including name and location of the quarry, name or position of the natural rock, date when sample was taken and trade-name or grade of stone.

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, I	NEW DELHI 110002
Telephones: 331 01 31, 331 13 75	Telegrams: Manaksanstha (Common to all Offices)
Regional Offices: 🖕	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zaf NEW DELHI 110002	ar Marg, (331 01 31 / 331 13 75
*Eastern : 1/14 C. I. T. Scheme VII M, V. I. Maniktola, CALCUTTA 700054	P. Road, 36 24 99
Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036	2 18 43 3 16 41 41 24 42
Southern : C. I. T. Campus, MADRAS 60011	3 {41 25 19 (41 29 16
†Western : Manakalaya, E9 MIDC, Marol, An BOMBAY 400093	dheri (East), 6 32 92 95
Branch Offices:	
'Pushpak', Nurmohamed Shaikh Marg, Khanpu AHMADABAD 380001	ur. (26348 26349
Peenya Industrial Area 1st Stage, Bangalore BANGALORE 560058	e Tumkur Road (38 49 55 38 49 56
Gangotri Complex, 5th Floor, Bhadbhada Roa BHOPAL 462003	d, T. T. Nagar, ` 6 67 16
Plot No. 82/83, Lewis Road, BHUBANESHW/ 53/5, Ward No. 29, R.G. Barua Road, 5th Bye GUWAHATI 781003	AR 751002 5 36 27 elane, 3 31 77
5-8-56C L. N. Gupta Marg (Nampally Station HYDERABAD 500001	n Road) 23 10 83
R14 Yudhister Marg. C Scheme, JAIPUR 302	$\begin{array}{c} 005 \\ 6 \\ 98 \\ 32 \\ 1 \\ 005 \end{array}$
117/418 B Sarvodaya Nagar, KANPUR 20800	$ \begin{array}{c} 21 & 68 & 76 \\ 21 & 82 & 92 \end{array} $
Patliputra Industrial Estate, PATNA 800013	6 23 05
T.C. No. 14/1421. University P.O., Palayam TRIVANDRUM 695035	{6 21 04 {6 21 17
Inspection Offices (With Sale Point):	
Pushpanjali, First Floor, 205-A West High Con Shankar Nagar Square, NAGPUR 440010	urt Road, 2 51 71
Institution of Engineers (India) Building, 133 PUNE 411005	2 Shivaji Nagar, 52435
•Sales Office in Calcutta is at 5 Chowringhee App Street, Calcutta 700072	roach, P. O. Princep 27 68 00
Bombay 400007 ‡Sales Office in Bangalore is at Unity Building, Na	uers, Grant Road, 89 05 20 arasimharaja Square, 22 36 71
Bangalore 560002	

Reprography Unit, BIS, New Delhi, India