

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 11276 (1985): Method of test for determination of openness or fiberization of chrysotile asbestos fibre by air permeability method using rapid surface area apparatus [CED 53: Cement Matrix Products]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



Indian Standard

METHOD OF TEST FOR
DETERMINATION OF OPENNESS OR
FIBERIZATION OF CHRYSOTILE ASBESTOS
FIBRE BY AIR PERMEABILITY METHOD
USING RAPID SURFACE AREA APPARATUS

UDC 677.511 : 620.193.29



© Copyright 1985

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

METHOD OF TEST FOR DETERMINATION OF OPENNESS OR FIBERIZATION OF CHRYSOTILE ASBESTOS FIBRE BY AIR PERMEABILITY METHOD USING RAPID SURFACE AREA APPARATUS

Cement and Concrete Sectional Committee, BDC 2

Chairman

DR H. C. VISVESVARAYA

Representing

Cement Research Institute of India, New Delhi

Members

ADDITIONAL DIRECTOR STANDARDS (B & S)	Research, Designs & Standards Organization (Ministry of Railways), Lucknow
DEPUTY DIRECTOR STANDARDS (B & S) (<i>Alternate</i>)	
SHRI K. P. BANERJEE	Larsen and Toubro Limited, Bombay
SHRI HARISH N. MALANI (<i>Alternate</i>)	
SHRI S. K. BANERJEE	National Test House, Calcutta
CHIEF ENGINEER (BD)	Bhakra Beas Management Board, Nangal Township
SHRI J. C. BASUR (<i>Alternate</i>)	
CHIEF ENGINEER (DESIGNS)	Central Public Works Department, New Delhi
EXECUTIVE ENGINEER (D) III (<i>Alternate</i>)	
CHIEF ENGINEER (RESEARCH- cum-DIRECTOR)	Irrigation and Power Research Institute, Government of Punjab, Amritsar
RESEARCH OFFICER (CONCRETE TECHNOLOGY) (<i>Alternate</i>)	
DIRECTOR	A. P. Engineering Research Laboratories, Hyderabad
JOINT DIRECTOR (<i>Alternate</i>)	
DIRECTOR	Central Soil and Materials Research Station, New Delhi
CHIEF RESEARCH OFFICER (<i>Alternate</i>)	
DIRECTOR (C & MDD-I)	Central Water Commission, New Delhi
DEPUTY DIRECTOR (C&MDD-I) (<i>Alternate</i>)	
SHRI V. K. GHANEKAR	Structural Engineering Research Centre (CSIR), Roorkee
SHRI A. V. GOKAK	Cement Controller (Ministry of Industry), New Delhi
SHRI S. S. MIGLANI (<i>Alternate</i>)	
SHRI A. K. GUPTA	Hyderabad Asbestos Cement Products Limited, Ballabgarh

(Continued on page 2)

© Copyright 1985

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

Members	Representing
SHRI P. J. JAGUS	Associated Cement Companies Ltd, Bombay
DR A. K. CHATTERJEE (Alternate)	
SHRI N. G. JOSHI	Indian Hume Pipes Co Limited, Bombay
SHRI R. L. KAPOOR	Ministry of Shipping and Transport (Roads Wing)
SHRI N. SIVAGURU (Alternate)	
SHRI S. K. LAHA	Institution of Engineers (India), Calcutta
SHRI B. T. UNWALLA (Alternate)	
DR A. K. MULLICK	Cement Research Institute of India, New Delhi
SHRI K. K. NAMBIAR	In personal capacity ('Ramanalaya' 11, First Crescent Park Road, Gandhinagar, Adyar, Madras)
SHRI S. N. PAL	M. N. Dastur and Company Private Limited, Calcutta
SHRI BIMAN DASGUPTA (Alternate)	
SHRI H. S. PASRICHA	Hindustan Prefab Limited, New Delhi
SHRI Y. R. PHULL	Indian Roads Congress, New Delhi; and Central Road Research Institute (CSIR), New Delhi
SHRI M. R. CHATTERJEE (Alternate)	Central Road Research Institute (CSIR), New Delhi
DR MOHAN RAI	Central Building Research Institute (CSIR), Roorkee
DR S. S. REHSI (Alternate)	
SHRI P. S. RAMACHANDRAN	India Cements Limited, Madras
DR M. RAMAIAH	Structural Engineering Research Centre (CSIR), Madras
DR A. G. MADHAVA RAO (Alternate)	
SHRI A. V. RAMANA	Dalmia Cement (Bharat) Limited, New Delhi
DR K. C. NARANG (Alternate)	
SHRI G. RAMDAS	Directorate General of Supplies and Disposals, New Delhi
DR A. V. R. RAO	National Buildings Organization, New Delhi
SHRI J. SEN GUPTA (Alternate)	
SHRI R. V. CHALAPATHI RAO	Geological Survey of India, Calcutta
SHRI S. ROY (Alternate)	
SHRI T. N. SUBBA RAO	Gammon India Limited, Bombay
SHRI S. A. REDDI (Alternate)	
SHRI ARJUN RIJHSINGHANI	Cement Corporation of India, New Delhi
SHRI C. S. SHARMA (Alternate)	
SHRI H. S. SATYANARAYANA	Engineer-in-Chief's Branch, Army Headquarters, New Delhi
SHRI V. R. KOTNIS (Alternate)	
SECRETARY	Central Board of Irrigation and Power, New Delhi
SHRI K. R. SAXENA (Alternate)	
SUPERINTENDING ENGINEER (DESIGNS)	Public Works Department, Government of Tamil Nadu, Madras
EXECUTIVE ENGINEER (SMD DIVISION) (Alternate)	
SHRI L. SWAROOP	Orissa Cement Limited, New Delhi
SHRI H. BHATTACHARYYA (Alternate)	
SHRI G. RAMAN, Director (Civ Engg)	Director General, ISI (Ex-officio Member)

Secretary

SHRI N. C. BANDYOPADHYAY
Deputy Director (Civ Engg), ISI

(Continued on page 9)

Indian Standard

METHOD OF TEST FOR DETERMINATION OF OPENNESS OR FIBERIZATION OF CHRYSOTILE ASBESTOS FIBRE BY AIR PERMEABILITY METHOD USING RAPID SURFACE AREA APPARATUS

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 12 April 1985, after the draft finalized by the Cement and Concrete Sectional Committee had been approved by the Civil Engineering Division Council.

0.2 A series of standards on testing procedures of asbestos fibre is being formulated so as to provide standard methods for obtaining physical and chemical properties of asbestos fibre which is used for manufacturing various asbestos cement products like asbestos cement sheets, asbestos cement pipes, etc. These testing procedures will be useful for both mine owners and the manufacturers of asbestos cement products.

0.3 The degree of fiberization or subdivisions of the asbestos fibre bundles in a specimen is related to its resistance to air flow. The number and size of the pores in the specimen are a function of the size of the fibre bundles and determine the resistance to air flow through the plug. In this method of test, the resistance to air flow of a compressed specimen of fixed mass and volume to a fixed hydraulic pressure head is determined.

0.4 In the formulation of this standard due weightage has been given to international coordination among the standards and practices prevailing in different countries in addition to relating it to the practices in the field in this country. This has been met by basing the standard on 'Chrysotile Asbestos Test Manual' 1974 (*revised* 1978) of Asbestos Textile Institute and Quebec Asbestos Mining Association.

0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS : 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

*Rules for rounding off numerical values (*revised*).

1. SCOPE

1.1 This standard covers the procedure for measuring the relative degree of openness or fiberization of milled chrysotile asbestos fibre by air permeability using rapid surface area apparatus.

1.2 This method is limited to fibres with an effective surface area in the range from 1 000 to 25 000 cm²/g. Samples containing excessive quantities of non-fibrous particles or contaminants will not give reliable or meaningful results.

2. SAMPLING

2.1 The sampling shall be carried out in accordance with IS : 4844-1968*.

3. PREPARATION OF TEST SAMPLE

3.1 The sample shall be spread on a smooth working surface in layers to form a flat pile of uniform thickness of approximately 13 mm and quartered.

3.2 Opposite quarters shall then be set aside and procedure as in **3.1** shall be repeated with the remaining quarters. Two 50 ± 0.1 g mass test specimens shall be selected by taking pinches from each quarter of the pile.


3.3 When pinches are taken, care shall be taken to include the total cross-section of the pile from top to bottom at the point where it is taken, including any grit or fines that may have segregated to the bottom. Any lumps or knots of matted fibre still remaining in the specimen should be disentangled before cell loading is begun.

4. APPARATUS

4.1 The apparatus consists of a rapid surface area tester including 50 g brass sample cell complete with perforated plate, end cap, retaining ring and base. A schematic diagram of the apparatus is shown in Fig. 1.

NOTE — The sample cell is made of brass such that the effective length occupied by the specimen is 58.903 ± 0.050 mm and the diameter is 38.964 ± 0.050 mm. It is advisable to check these dimensions periodically.

*Method of sampling and preparation of asbestos fibre for laboratory test purposes.



LEGEND

<i>A</i> — Supply of clean compressed air	<i>J</i> — Test specimen
<i>B</i> — Control valve	<i>K</i> — Air outlet
<i>C</i> — Water reservoir	<i>L</i> — Shut-off valve
<i>D</i> — Bubbler tube	<i>M</i> — Dust filter (Fibre glass)
<i>E</i> — Capillary resistance	<i>N</i> — Capillary snubber
<i>F</i> — Manometer leg	<i>O</i> — Zero mark on manometer
<i>G</i> — Manometer scale (Exponential)	<i>P</i> — Air dryer or desiccator (Dryerite)
<i>H</i> — Permeability cell	

NOTE — Items *A*, *L*, & *P* are not supplied with the apparatus.

FIG. 1 SCHEMATIC DIAGRAM OF RAPID SURFACE AREA TESTER

4.2 Accessories — The accessories shall be the following:

- source of clean air at approximately 14 kPa,
- calibrating standards as described in 4.3,
- handle for inserting and extracting capillary tube holders in the permeability cell,
- tamping rod, and
- filling funnel.

4.3 Calibrating Standards — The calibrating standards (low and high) consist of capillary glass tubing mounted in a holder which suitably fills the specimen cavity in the permeability cell and shall have the following requirements:

a) *Low Standard*

Surface area range	4 500 to 5 500 cm ² /g
Glass capillary tube bore	0.311 ± 0.012 mm
Length	13 mm, approximately

b) *High Standard*

Surface area range	20 000 to 23 000 cm ² /g
Glass capillary tube bore	0.178 ± 0.013 mm
Length	39.5 mm, approximately

NOTE 1 — For accurate results, calibrating standards shall be kept in airtight containers or in a desiccator when not in use.

NOTE 2 — Capillary tubes shall be cleaned with dry, compressed air, free from contaminants, at 138 kPa, if permanently mounted or 34.5 kPa, if temporarily mounted prior to calibration by allowing the air to flow 60 seconds.

5. PREPARATION OF APPARATUS

5.1 The apparatus shall be checked daily before using and adjustments made, if necessary, in accordance with 5.1.1 to 5.1.5.

5.1.1 Verify the zero reading of the tester as given in 7.4 and 7.5 but with the cell empty.

5.1.2 In case the manometer does not read zero, check to determine if the manometer is out of plumb.

5.1.3 If the water level is below zero, adjust by adding distilled water through the hole in the reservoir cap.

5.1.4 If the water level is above zero, correct it by inserting a wick through the hole to remove excess water. The apparatus should not be tilted.

5.1.5 Ensure that the perforated disc is perfectly seated at the bottom of the sample cell.

6. INSTRUMENT CALIBRATION

6.1 Prepare the apparatus as described in 5.

6.2 Insert a calibrating standard mounted in its capillary tube holder into the cell using the handle. Insert the end cap of the cell, and screw down the retaining ring using the key and base provided, until there is a positive resistance indicating that the O-ring seal is fully compressed and that metal-to-metal contact has been established between the cell face and the end cap.

6.3 Proceed as in 7.4 and 7.5. If the results differ from the nominal value of the standard by more than ± 3.0 percent, it may be concluded that the equipment is defective and the defect must be rectified before proceeding further.

7. PROCEDURE

7.1 Place the filling funnel over the open end of the cell and empty one 50 g specimen into it in stages, using the tamping rod at intervals to coax all the specimen past the neck of the funnel. Trapping of any fibre between the rod and the funnel shall be avoided. In a single motion, press the specimen into the cell until the transverse bar touches the upper edge of the filling funnel.

7.2 Do not compress the fibre in the cell without the filling funnel in place.

7.3 Withdraw the rod slowly, rotating it slightly to ensure that the compressed fibre is not disturbed. Insert the end cap of the cell, and screw down the retaining ring using the key and base provided, until there is a positive resistance indicating that the O-ring seal is fully compressed and the metal-to-metal contact has been established between the cell face and the end cap.

7.4 Connect the cell to the rubber discharge tube of the tester and turn on the air supply. Open the control valve on the apparatus until the water level in the front manometer tube begins to fall. When air bubbles begin to escape from the escape holes at the bottom end of the brass tube in the transparent vertical cylinder at the rear of the tester, adjust the control valve until bubbles escape at a rate of about three per second.

7.5 When the water level in the manometer tube appears to be stationary, note the scale reading opposite this level. Wait 10 seconds and read the level again to ensure that it is constant; if not, take another reading after a further 10 seconds. Estimate the scale reading to half a division, and note down this reading as the effective surface area in square centimetres per gram.

7.6 When the reading has been noted, close the shut-off valve, and disconnect the cell from the apparatus. The setting of the control valve shall not be changed, unless required.

7.7 Repeat the procedure described in **7.1** to **7.6** for the second test specimen.

8. REPORTING OF RESULTS

8.1 Fully identify the sample stating the origin and the designation. Calculate the average of the two readings.

8.2 If the difference between any individual readings and the average is more than 3 percent, the test shall be repeated.

(Continued from page 2)

Asbestos Cement Products Subcommittee, BDC 2 : 3

Convener

DR S. K. CHOPRA
S-436 Greater Kailash, New Delhi

Members

SHRI S. K. BANERJEE
SHRI S. N. BASU

Representing

National Test House, Calcutta
Directorate General of Supply and Disposals, New Delhi

SHRI T. N. OBOVEJA (Alternate)
SHRI K. S. CHAYAMURTHY

Engineer-in-Chief Branch, Army Headquarters, New Delhi

SHRI K. R. BHAMBANI (Alternate)
DIRECTOR STANDARDS (B & S)-I

Research, Designs and Standards Organization
(Ministry of Railways), Lucknow

ASSISTANT DIRECTOR STANDARDS
(B & S)-II (Alternate)

SHRI K. D. DHARIYAL

Central Building Research Institute (CSIR),
Roorkee

SHRI S. GANAPATHY

Southern Asbestos Cements Ltd, Madras

GENERAL MANAGER (CEMENT)

Rohtas Industries Ltd, Dalmianagar

SHRI D. N. SINGH (Alternate)

SHRI S. S. GOENKA

Sarbamangala Manufacturing Co, Calcutta

SHRI I. P. GOENKA (Alternate)

SHRI S. K. GHOSH

Directorate General of Technical Development,
New Delhi

SHRI M. L. DABRAL (Alternate)

SHRI SRINIVASAN N. IYER

Everest Building Products Ltd, Bombay

DR V. G. UPADHYAYA (Alternate)

SHRI P. S. KALANI

Saurabh Construction Co, Indore

DR (SHRIMATI) S. LAXMI

Cement Research Institute of India, New Delhi

SHRI HARSHAD R. OZA

Flow Asbestos Products, Ahmadabad

SHRI V. PATTABHI

Hyderabad Asbestos Cement Products Ltd,
Hyderabad

SHRI A. K. GUPTA (Alternate)

SHRI R. V. CHALAPATHI RAO

Geological Survey of India, Calcutta

SHRI S. ROY (Alternate)

DR A. V. R. RAO

National Buildings Organization, New Delhi

SHRI J. SEN GUPTA (Alternate)

SHRI L. T. P. SINHA

Small Scale Industries, New Delhi

SHRI V. N. SOMANI

Shree Digvijay Cement Co Ltd, Bombay

SHRI S. R. BHANDARI (Alternate I)

SHRI J. J. SHAH (Alternate II)

SUPERINTENDING SURVEYOR OF
WORKS (CZ)

Central Public Works Department, New Delhi

SURVEYOR OF WORKS (CZ) (Alternate)

SHRI S. A. SWAMY

Municipal Corporation of Delhi, Delhi

(Continued on page 10)

(Continued from page 9)

Panel for Indigenous Varieties of Asbestos, BDC 2 : 3/P1

Members

SHRI G. M. BANERJEA
CONTROLLER

SHRI R. K. SINHA (Alternate)

DEPUTY DIRECTOR

SHRI K. D. DHARIYAL

GENERAL MANAGER (CEMENT)

SHRI D. N. SINGH (Alternate)

SHRI S. K. GHOSH

SHRI M. L. DABRAL (Alternate)

DR S. P. GHOSH

SHRI M. V. RANGA RAO (Alternate)

SHRI SRINIVASAN N. IYER

DR V. G. UPADHYAYA (Alternate)

SETH PUSALAL MANSINGHKA

DR A. V. R. RAO

SHRI J. SEN GUPTA (Alternate)

SHRI A. V. S. R. SASTRI

SHRI PALVINDER SINGH (Alternate)

SHRI V. N. SOMANI

SHRI S. R. BHANDARI (Alternate I)

SHRI J. J. SHAH (Alternate II)

DR I. D. VARMA

SHRI N. VENKATARAMAN

Representing

Geological Survey of India, Calcutta
Indian Bureau of Mines, Nagpur

Central Fuel Research Institute (CSIR), Jealgora
Central Building Research Institute (CSIR),
Roorkee

Rohtas Industries Ltd, Dalmianagar

Directorate General of Technical Development, New
Delhi

Cement Research Institute of India, New Delhi

Everest Building Products Ltd, Bombay

Pusalal Mansinghka Pvt Ltd, Bhilwara

National Buildings Organization, New Delhi

Associated Instrument Manufacturers (India) Ltd,
New Delhi

Shree Digvijay Cement Co Ltd, Ahmadabad

Hyderabad Asbestos Cement Products Ltd,
Hyderabad

Hindustan Ferodo Ltd, Bombay