

X

इंटरनेट

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

"जानने का अधिकार, जीने का अधिकार" Mazdoor Kisan Shakti Sangathan "The Right to Information, The Right to Live"

"पुराने को छोड नये के तरफ" Jawaharlal Nehru "Step Out From the Old to the New"

मानक

IS 11629 (1986): Code of practice for installation and operation of single point hydraulic over-flow setting gauge

[CED 43: Soil and Foundation Engineering]

611111111

Made Available By Public, Resource, Org



"ज्ञान से एक नये भारत का निर्माण″ Satyanarayan Gangaram Pitroda "Invent a New India Using Knowledge"

RIGHT TO INFORMATION "ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता Bhartrhari-Nītiśatakam "Knowledge is such a treasure which cannot be stolen"



BLANK PAGE



PROTECTED BY COPYRIGHT

COMPLIMENTARY COPY

IS: 11629 - 1986

Indian Standard CODE OF PRACTICE FOR INSTALLATION AND OPERATION OF SINGLE POINT HYDRAULIC OVER-FLOW SETTING GAUGE

UDC 681-128:681-121-873:006-76



© Copyright 1986

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

December 1986

Indian Standard

CODE OF PRACTICE FOR INSTALLATION AND OPERATION OF SINGLE POINT HYDRAULIC OVER-FLOW SETTING GAUGE

Foundation Engineering Sectional Committee, BDC 43

Chairman	Representing			
Maj-Gen Ombir Singh	Ministry of Defence			
Members				
Col K. P. ANAND (Alternate t Maj-Gen Ombir Singh)	0			
Additional Director (GE) Additional Director (S) (Alternate)	Ministry of Railways (RDSO)			
SHRI K. K. AGGARWAL	Posts & Telegraph Department, New Delhi			
Shri B. Anjiah	A.P. Engineering Research Laboratories, Hyderabad			
Shri Arjun Rijhsinghani	Cement Corporation of India, New Delhi			
SHRI O. S. SRIVASTAVA (Alteri	nate)			
DR R. K. BHANDARI	Central Building Research Institute (CSIR), Roorkee			
Shri Chandra Prakash (Alte	rnate)			
SHRI MAHABIR BIDASARIA	Ferro-Concrete Consultants Pvt Ltd, Indore			
SHRI ASHOK BIDASARIA (Alter.	nate)			
SHRI S. P. CHAKRABARTI	Ministry of Transport (Roads Wing)			
SHRI P. K. DUTTA (Alternate				
SHRI A. K. CHATTERJEE	Gammon India Ltd, Bombay			
SHRI A. C. ROY (Alternate)				
CHIEF ENGINEER	Calcutta Port Trust, Calcutta			
SHRI S. GUHA (Alternate)	Simular Constate Biles (I) But I til Coloutte			
SHRIK, K. DAS GUPTA	Simplex Concrete Piles (1) Pvt Ltd, Calcutta			
SHRI H, GUHA BISWAS (Altern	ule) In normanal canonity (5 Hunderford County 101 Hund			
SHRI A. G. DASTIDAR	gerford Street, Calcutta)			
Shri V. C. Deshpande	Pressure Piling Co (I) Pvt Ltd, Bombay			
DIRECTOR (CSMRS)	Central Soil and Materials Research Station, New Delhi			
CHIEF RESEARCH OFFICER (CSMRS)(Alternate)				

(Continued on page 2)

© Copyright 1986

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

Members	Representing		
Shri A. H. Divanji	Asia Foundations and Construction Private Limited, Bombay		
SHRI A. N. JANGLE (Alternate	·) ·		
SHRI A. GHOSHAL	Stup Consultants Limited, Bombay		
DR GOPAL RANJAN	University of Roorkee, Roorkee		
SHRI N. JAGANNATH	Steel Authority of India Ltd. Durgapur		
SHRI A. K. MITRA (Alternate)		
SHRI ASHOK K. JAIN	G. S. Jain & Associates, New Delhi		
SHRI VIJAY KUMAR JAIN (Alte	rnate)		
JOINT DIRECTOR (DESIGN)	National Buildings Organization, New Delhi		
SHRI SUNIL BERY (Alternate)			
DR R. K. KATTI	Indian Institute of Technology, Bombay		
SHRI S. R. KULKARNI	M. N. Dastur & Company Pyt Ltd. Calcutta		
SHRI S. ROY (Alternate)			
SHRI A. P. MATHUR	Central Warehousing Corporation, New Delhi		
SHRI V. B. MATHUR	Mackenzies Ltd. Bombay		
SHRI S. MUKHERIEE	In personal capacity (E-104 A. Simla House, Nenean		
	Sea Road, Bombay)		
SHRI T. K. D. MUNSI	Engineers India Limited, New Delhi		
SHRI M. IYENGAR (Alternate)			
SHRI A. V. S. R. MURTY	Indian Geotechnical Society, New Delhi		
SHRI B. K. PANTHAKY	Hindustan Construction Co Ltd. Bombay		
SHRI V. M. MADGE (Alternate)		
SHRI M. R. PUNIA	Cemindia Company Ltd. Bombay		
SHRI D. J. KETKAR (Alternate)		
DR V. V. S. RAO	Nagadi Consultants Private Limited, New Delhi		
DR A. SARGUNAN	College of Engineering, Guindy, Madras		
SHRI S. BOMMINATHAN (Altern	ate)		
SUPERINTENDING ENGINEER	Central Public Works Department, New Delhi		
(DESIGNS)	,		
EXECUTIVE ENGINEER (DESIGNS	SV)		
(Alternate)	,		
Dr A. Varadarajan	Indian Institute of Technology, New Delhi		
DR R. KANIRAJ (Alternate)			
Shri G. Raman,	Director General, ISI (Ex-officio Member)		
Director (Civ Engg)			

Secretary

SHRI K. M. MATHUR Joint Director (Civ Engg), ISI

Foundation Instrumentation Subcommittee, BDC 43:7

Convener

DR R. K. BHANDARI

Central Building Research Institute (CSIR), Roorkee

Members

SHRI K. N. BARTAR

Pie Roorkee (India), Roorkee Engineers India Ltd, New Delhi SHRI M. IYENGAR DR R. K. M. BHANDARI (Alternate)

(Continued on page 7)

Indian Standard

CODE OF PRACTICE FOR INSTALLATION AND OPERATION OF SINGLE POINT HYDRAULIC OVER-FLOW SETTING GAUGE

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 30 January 1986, after the draft finalized by the Foundation Engineering Sectional Committee had been approved by the Civil Engineering Division Council.

0.2 Hydraulic over-flow settlement gauge is a simple device used for measuring settlements of earthfill like ground; embankments and dams. This standard is being formulated so as to cover detail guidance in regard to installation and operation of such single point type of gauge which is commonly used.

0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standrad covers details of installation and operation of single point hydraulic over-flow settlement gauge.

2. GENERAL

2.1 Hydraulic over-flow settlement gauge is essentially a instrument which works on the principle of manometer and is thus basically a large U-tube. Its one end is in the form of a measuring stand pipe (manometer) located in a remotely built instrument house and the other end is an over-flow tube terminating in the settlement capsule.

^{*}Rules for rounding off numerical values (revised).

2.2 The unit comprises (a) a cylindrical settlement capsule (cell) of glass/ Pvc (b) a rigid transparent measuring glass/Pvc stand pipe which shall a metre high and (c) a set of three Pvc/glass tubes that is drain tube, air line tube and water over-flow tube with brass leak proof connections. Each of these tubes shall be not less than 30 m long (see Fig. 1).

3. INSTALLATION AND OPERATION (see Fig. 1)

3.1 The three tubes should be connected at the appropriate junctions at the bottom of the settlement cell through leak proof connections and the cell should be installed vertically within the fill or the subgrade at the elevation where measurements are required. The cell should then be encased in concrete. The tubings from the cell should be laid in a shallow trench leading to the instrument house. In order to assist quick drainage of the water from the cell, a minimum longitudinal slope of 1 in 100 should be provided in trench bottom towards instrument house. The tubings should be coated with minimum 50 mm thick bentonite layer of working consistency and the trench backfilled with sand or soil to avoid stones damaging the tubes. A reference level is marked on the outside of each gauge in order to check the initial reading.

3.2 The height of the stand pipe should be selected so as to cover up the elevation of the cell unit and its anticipated settlement.

3.3 When the centre of the scale of the stand pipe is at the same level as the upper end of the over-flow tube in the settlement cell, the air pressure acting on both is the same. The elevation of the over-flow level in the cell is then read out on the scale attached to the stand pipe.

3.4 If it is not possible to have the buried settlement cell and the stand pipe at the same level, the air pressure in the stand pipe can be increased or reduced by a column of water. At rest (stabilization), the water level stands in the stand pipe lowered or raised by exactly the height of the additional water column.

3.5 The gauge should have an accuracy of ± 1 mm when the stand pipe is at the same height as the cell and ± 2 mm when the water column is used.

4. PROCEDURE

4.1 The system is primed by passing de-aired water from the read-out location to the cell via the water tube, and back through the drain tube. This circulation should be continued until all air has been removed from the water tube.

4.2 The water supply valve is then closed, and air pressure applied to the top of the cell through the air line. All water, except that in the cylinder and water tube should be expelled and a continuous stream of air should be noted at the read out station through the drain tube.

4.3 The water level in the cell should then be at A as shown in Fig. 1 and the cell should be at the atmospheric pressure through the air tube. This level is noted in the stand pipe after connecting the same to the cell and adjusting it to the stabilized point.

4.4 Any subsequent settlement of the strate should cause a corresponding settlement of the cell, thus causing a variation in the level of the water column in the stand pipe. The changed level should be recorded after making necessary adjustments. The difference between initial and final levels of stand pipe water column level indicates the settlement at the level of the cell.

5. PRECAUTIONS

5.1 Before taking measurements, the over-flow tube should be de-aired. If necessary, a slight suction may be applied through the drain tube to facilitate drainage of the over-flow water. To take care of the effect of temperature of water, it should be flushed with de-aired water before each measurement is taken.

5.2 All connections should be ensured to be leak-proof and a pair of spanners should be used to screw and unscrew the compression couplings.

5.3 The measuring unit should be installed outside the zone affected by settlement.

5.4 As the air tube has to maintain the over-flow and the stand pipe water surfaces at the same pressure it should be kept free from all kinds of obstructions such as water droplets and other such obstructions.



FIG. 1 DETAILS OF INSTALLATION OF SINGLE POINT HYDRAULIC SETTLEMENT GAUGE

(Continued from page 2)

M	emł	hers
	umu	1010

Representing

Shri Z. M. Karachiwala	Vasi Shums & Co Pvt Ltd, Bombay				
DR B. V. K. LAVANIA	University of Roorkee, Roorkee				
Shri P. K. Nagarkar	Maharashtra Engineering Research Institute, Nasik				
Shri M. K. Kulkarni (Altern	nate)				
SHRI M. D. NAIR	Associated Instrument Mfrs (1) Pvt Ltd, New Delhi				
SHRI A. V. SHASTRI (Alternate					
DR N. V. NAYAK	Asia Foundations & Constructions Ltd. Bombay				
Shri N, K, Oza	Ministry of Railways (RDSO)				
Shri V. M. Sharma	Central Soil and Materials Research Station,				
	New Delhi				
Prof N. Som	Jadavpur University, Calcutta				

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

Base Units

Quantity	Unit	Symbol	
Length	metre	m	
Mass	kilogram	kg	
Time	second	S	
Electric current	ampere	Α	
Thermodynamic temperature	kelvin	К	
Luminous intensity	candela	cd	
Amount of substance	mole	mol	
Supplementary Units			
Quantity	Unit	Symbol	
Plane angle	radian	rad	
Solid angle	steradian	sr	
Derived Units			
Quantity	Unit	Symbol	Definition
Force	newton	N	1 $N = 1 \text{ kg. } m/s^2$
Energy	joule	J	1 J = 1 N.m
Power	watt	W	1 W = 1 J/s
Flux	weber	Wb	1 Wb = 1 V.s
Flux density	tesla	Т	$1 T = 1 Wb/m^2$
Frequency	hertz	Hz	1 Hz = 1 c/s (s^{-1})
Electric conductance	siemens	S	1 S = 1 A/V
Electromotive force	volt	v	1 V = 1 W/A
Pressure, stress	pascal	Pa	1 $Pa = 1 N/m^2$
			•