

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 11770-1 (1987): Recommendations for control of emission of asbestos dust in premises manufacturing products containing asbestos, Part 1: Asbestos cement products [CED 53: Cement Matrix Products]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



Indian Standard

RECOMMENDATIONS FOR
CONTROL OF EMISSION OF ASBESTOS
DUST IN PREMISES MANUFACTURING
PRODUCTS CONTAINING ASBESTOS

PART 1 ASBESTOS CEMENT PRODUCTS

UDC 666·961 : 628·511 : 658·382·1

© Copyright 1987

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

RECOMMENDATIONS FOR CONTROL OF EMISSION OF ASBESTOS DUST IN PREMISES MANUFACTURING PRODUCTS CONTAINING ASBESTOS

PART 1 ASBESTOS CEMENT PRODUCTS

Cement and Concrete Sectional Committee, BDC 2

Chairman

DR H. C. VISVESVARAYA

Representing

National Council for Cement and Building Materials,
New Delhi

Members

ADDITIONAL DIRECTOR STANDARDS (B & S)	Research, Designs & Standards Organization (Ministry of Railways), Lucknow
DEPUTY DIRECTOR STANDARDS (B & S) (<i>Alternate</i>)	
SHRI K. P. BANERJEE	Larsen and Toubro Limited, Bombay
SHRI HARISH N. MALANI (<i>Alternate</i>)	
SHRI S. K. BANERJEE	National Test House, Calcutta
CHIEF ENGINEER (BD)	Bhakra Beas Management Board, Nangal Township
SHRI J. C. BASUR (<i>Alternate</i>)	
CHIEF ENGINEER (DESIGNS)	Central Public Works Department, New Delhi
EXECUTIVE ENGINEER (D)-III (<i>Alternate</i>)	
CHIEF ENGINEER (RESEARCH) - cum-DIRECTOR	Irrigation and Power Research Institute, Amritsar
RESEARCH OFFICER (CONCRETE TECHNOLOGY) (<i>Alternate</i>)	
DIRECTOR	A. P. Engineering Research Laboratories, Hyderabad
JOINT DIRECTOR (<i>Alternate</i>)	
DIRECTOR	Central Soil and Materials Research Station, New Delhi
CHIEF RESEARCH OFFICER (<i>Alternate</i>)	
DIRECTOR (CMDD-I)	Central Water Commission, New Delhi
DEPUTY DIRECTOR (CMDD-I) (<i>Alternate</i>)	
SHRI V. K. GHANEKAR	Structural Engineering Research Centre (CSIR), Roorkee
SHRI S. GOPINATH	The India Cements Ltd, Madras
SHRI T. TAMILAKERAN (<i>Alternate</i>)	

(Continued on page 2)

© Copyright 1987

BUREAU OF INDIAN STANDARDS

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

<i>Members</i>	<i>Representing</i>
SHRI A. K. GUPTA	Hyderabad Industries Limited, Hyderabad
SHRI P. J. JAGUS	Associated Cement Companies Ltd, Bombay
DR A. K. CHATTERJEE (<i>Alternate</i>)	
SHRI N. G. JOSHI	Indian Hume Pipes Co Ltd, Bombay
SHRI R. L. KAPOOR	Ministry of Transport (Department of Surface Transport) (Roads Wing)
SHRI R. K. SAXENA (<i>Alternate</i>)	
SHRI S. K. LAHA	The Institution of Engineers (India), Calcutta
SHRI B. T. UNWALLA (<i>Alternate</i>)	
DR A. K. MULLICK	National Council for Cement and Building Materials, New Delhi
SHRI S. N. PAL	M. N. Dastur and Co Pvt Ltd, Calcutta
SHRI BIMAN DASGUPTA (<i>Alternate</i>)	
SHRI H. S. PASRICHA	Hindustan Prefab Ltd, New Delhi
SHRI Y. R. PHULL	Indian Roads Congress, New Delhi; and Central Road Research Institute (CSIR), New Delhi
SHRI M. R. CHATTERJEE (<i>Alternate</i>)	Central Road Research Institute (CSIR), New Delhi
DR MOHAN RAI	Central Building Research Institute (CSIR), Roorkee
DR S. S. REHSI (<i>Alternate</i>)	
SHRI A. V. RAMANA	Dalmia Cement (Bharat) Ltd, New Delhi
DR K. C. NARANG (<i>Alternate</i>)	
DR M. RAMAIAH	Structural Engineering Research Centre (CSIR), Madras
DR A. G. MADHAVA RAO (<i>Alternate</i>)	
SHRI G. RAMDAS	Directorate General of Supplies and Disposals, New Delhi
DR A. V. R. RAO	National Buildings Organization, New Delhi
SHRI J. SEN GUPTA (<i>Alternate</i>)	
SHRI T. N. SUBBA RAO	Gammon India Ltd, Bombay
SHRI S. A. REDDI (<i>Alternate</i>)	
SHRI A. U. RIJHSINGHANI	Cement Corporation of India, New Delhi
SHRI C. S. SHARMA (<i>Alternate</i>)	
SHRI H. S. SATYANARAYANA	Engineer-in-Chief's Branch, Army Headquarters, New Delhi
SHRI V. R. KOTNIS (<i>Alternate</i>)	
SECRETARY	Central Board of Irrigation and Power, New Delhi
SHRI K. R. SAXENA (<i>Alternate</i>)	
SHRI R. K. SINHA	Development Commissioner for Cement Industry (Ministry of Industry), New Delhi
SHRI S. S. MIGLANI (<i>Alternate</i>)	
SUPERINTENDING ENGINEER (DESIGNS)	Public Works Department, Government of Tamil Nadu, Madras
EXECUTIVE ENGINEER (SMR DIVISION) (<i>Alternate</i>)	
SHRI L. SWAROOP	Orissa Cement Ltd, New Delhi
SHRI H. BHATTACHARYA (<i>Alternate</i>)	
SHRI S. K. GUHA THAKURTA	Gannon Dunkerley & Co Ltd, Bombay
SHRI S. P. SANKARNARAYANAN (<i>Alternate</i>)	
SHRI G. RAMAN, Director (Civ Engg)	Director General, BIS (<i>Ex-officio Member</i>)

Secretary

SHRI N. C. BANDYOPADHYAY
Deputy Director (Civ Engg), BIS

(Continued on page 10)

Indian Standard

RECOMMENDATIONS FOR CONTROL OF EMISSION OF ASBESTOS DUST IN PREMISES MANUFACTURING PRODUCTS CONTAINING ASBESTOS

PART 1 ASBESTOS CEMENT PRODUCTS

0. FOREWORD

0.1 This Indian Standard was adopted by the Bureau of Indian Standards on 30 July 1987, after the draft finalized by the Cement and Concrete Sectional Committee had been approved by the Civil Engineering Division Council.

0.2 In recent years there has been a growing awareness that exposure to asbestos dust can have harmful effects on the health of workers. In order to give guidelines on how the risk of exposure to asbestos dust can be prevented, controlled or minimized, it was felt necessary to lay down some standards regarding safe use of different products containing asbestos, improving conditions in workplaces, preventive measures, protection and supervision of the health of workers, packaging and transport of asbestos, disposal of asbestos waste, etc. This standard laying down the recommendations for control of emission of asbestos dust in premises manufacturing products containing asbestos, has been prepared in three parts. This part lays down the recommendations for control of emission of asbestos dust in premises manufacturing asbestos cement products. Recommendations for control of emission of asbestos dust in premises manufacturing friction materials containing asbestos and non-cement asbestos products other than friction materials are covered in Parts 2 and 3 respectively. The concentration of airborne asbestos dust in work environment shall be determined in accordance with the method given in IS : 11450-1986*.

0.3 In the formulation of this standard due weightage has been given to international co-ordination among the standards and practices prevailing in different countries in addition to relating it to the practices in the field in this country. This has been met by deriving assistance from 'ILO Codes of Practice: Safety in the Use of Asbestos', 1984 published by the International Labour Office, Geneva.

*Method for determination of airborne asbestos fibre concentration in work environment by light microscopy (membrane filter method).

0.4 This standard is one of a series of Indian Standards on safety in handling and use of asbestos. Other standards in the series already formulated and under preparation are as follows:

- IS : 11450-1986 Method of determination of airborne asbestos fibre concentration in work environment by light microscopy (membrane filter method)
- IS : 11451-1986 Recommendations for safety and health requirements relating to occupational exposure to asbestos
- IS : 11767-1986 Recommendations for cleaning of premises and plants using asbestos fibres
- IS : 11768-1986 Recommendations for disposal of asbestos waste material
- IS : 11769 (Part 1)-1987 Guidelines for safe use of products containing asbestos: Part 1 Asbestos cement products
- IS : 11769 (Part 2)-1986 Guidelines for safe use of products containing asbestos: Part 2 Friction materials
- IS : 11769 (Part 3)-1986 Guidelines for safe use of products containing asbestos: Part 3 Non-cement asbestos products other than friction materials
- IS : 11770 (Part 2)-1986 Recommendations for control of emission of asbestos dust in premises manufacturing products containing asbestos: Part 2 Friction materials
- IS : 11770 (Part 3)-1987 Recommendations for control of emission of asbestos dust in premises manufacturing products containing asbestos: Part 3 Non-cement asbestos products other than friction materials
- IS : 12078-1987 Recommendations for personal protection of workers engaged in handling asbestos
- IS : 12079-1987 Recommendations for packaging, transport and storage of asbestos
- IS : 12080-1987 Recommendations for local exhaust ventilation systems in premises manufacturing products containing asbestos
- IS : 12081 (Part 1)-1987 Recommendations for pictorial warning signs and precautionary notices for asbestos and products containing asbestos: Part 1 Workplaces
- IS : 12081 (Part 2)-1987 Recommendations for pictorial warning signs and precautionary notices for asbestos and products containing asbestos: Part 2 Asbestos and its products
- IS : 12082 (Part 1)-1987 Recommendations for control of asbestos emission: Part 1 Mining of asbestos ore

IS : 12082 (Part 2) Recommendations for control of asbestos emission: Part 2 Milling of asbestos (*under preparation*)

Method for determination of asbestos concentration in water (*under preparation*)

1. SCOPE

1.1 This standard lays down the recommendations for control of emission of asbestos dust in premises used for manufacturing asbestos cement products.

2. OBJECT

2.1 The object of this standard is to recommend procedures that shall be adopted in premises used for manufacturing asbestos cement products so as to minimize and control the emission of asbestos dust in the working environment for the safety of workers.

3. GENERAL REQUIREMENTS

3.1 All appropriate and practicable measures of engineering control, work practice and administrative control shall be adopted to eliminate or to minimize the asbestos dust concentration in the working environment to the lowest possible level.

3.2 Engineering Controls — Engineering controls shall include wetting, mechanical handling, ventilation and redesign of the process to eliminate, contain or collect asbestos dust emission by the following processes:

- a) Dust suppression — Use of wet methods, where appropriate;
- b) Dust dilution through:
 - 1) modification of dust generating system;
 - 2) process separation, automation, etc; and
 - 3) general ventilation of the working areas with clean air;
- c) Dust extraction by:
 - 1) enclosures/booths,
 - 2) well designed hoods, and
 - 3) vacuum cleaners for prevention of dust dissemination;
- d) Dust conveyance by balanced ductwork and adopting appropriate air velocities;
- e) Dust collection through the use of effective filters; and
- f) Separate workplace for those processes with potential to generate dust levels higher than permissible exposure limit.

3.2.1 Local Exhaust Ventilation

3.2.1.1 Where total enclosure of the dust-producing process is not practicable, local exhaust ventilation equipment shall be provided and maintained as given in IS : 12080-1987*.

3.2.1.2 For efficient operation, the exhaust ventilation shall be located as close as possible to the source of dust emission by the use of hoods, booths or enclosures.

3.2.1.3 The local exhaust system shall be designed to collect and remove all dust-laden air.

3.2.1.4 Openings in the enclosures shall be as small as possible while still allowing access to the necessary work operation.

3.2.1.5 In case of captor hoods and booths, the ventilation equipment shall be so constructed that air turbulence and eddies created by the work process or by the workers do not prevent the effective removal of dust.

3.3 Work Practices — Appropriate work practices shall be followed where materials or processes are used which may give rise to asbestos dust in the working environment. Such work practices shall include the following:

- a) Requirements to use and maintain properly process machinery, installations, equipment, tools, local exhaust and ventilation system;
- b) Regular cleaning of machinery and work areas by appropriate methods (*see* IS : 11767-1986†); and
- c) Proper use of personal protective equipment, where required (*see* IS : 12078-1987‡).

4. RECOMMENDED CONTROL FOR DIFFERENT OPERATIONS

4.1 Fibre Handling

4.1.1 Asbestos fibre shall be supplied only in closed containers, such as impermeable plastic bags.

4.1.2 As far as practicable, palletized handling shall be arranged to avoid damage of bags while handling and to facilitate mechanized handling.

4.1.3 In case any damaged bag is found during handling, the same shall be repaired by pasting adhesive tapes or by stitching the damaged area in such a way as to avoid escape of fibre into the atmosphere.

*Recommendations for local exhaust ventilation systems in premises manufacturing products containing asbestos.

†Recommendations for cleaning of premises and plants using asbestos fibres.

‡Recommendations for personal protection of workers engaged in handling asbestos.

4.2 Milling and Fibre Preparation

4.2.1 Milling of fibre shall be done in a fibre grinding mill which is covered and connected to a dust extraction system so as to extract the dust generated during charging and milling of the fibre.

4.2.2 Milling shall be done by wetting the fibre so that emission of dust is controlled.

4.2.3 Asbestos fibre supplied in plastic bags shall be opened only in an enclosed chamber connected to a dust extraction system under negative pressure so that leakage of dust to workplace is prevented.

4.2.3.1 The bags shall be opened and emptied automatically, whenever practicable.

4.2.4 The bags shall be placed as close as possible to the hopper or feed chamber.

4.2.5 The contents of the bags shall be discharged without the bag being shaken.

4.2.6 Empty bags shall be disposed of according to the provisions given in IS : 11768-1986*.

4.2.7 In no case blending of different grades of fibre shall be carried out in open. Partially discharged bags containing dry fibre shall not be stored outside the enclosure.

4.3 Handling Finished Products

4.3.1 At the final stage of manufacturing, or wherever asbestos cement products are being handled in large quantities, mechanical handling equipment shall be used when practicable.

4.3.2 Individual boards, sheets or other products, when moved manually, shall be placed with care on the stack or other resting site.

4.3.2.1 Dropping or dragging of finished product shall be avoided.

4.3.3 All storage of asbestos cement products on site shall be within a designated area. The designated area shall be maintained in a clean condition.

4.4 Finishing Operations

4.4.1 Suitable efficient dust extraction equipment along with well designed suction hood shall be provided to all finishing machine which turn, groove, chamfer and finish to avoid escaping of generated dust, while in operation. Low-volume, high-velocity air systems are usually most suitable for this purpose.

*Recommendations for disposal of asbestos waste material.

4.4.2 It is recommended that slow-running tools with hard metal teeth shall be used.

4.4.3 The equipment shall be designed to remove loose dust and swarf from the cut edges.

4.4.4 Where appropriate, boards shall be treated with a sealing solution for the suppression of dust on surfaces and edges.

NOTE — The recommendations given in **4.4.3** and **4.4.4** are applicable for low density asbestos cement products (density less than 1.20).

4.4.5 Boards and sheets shall be cut singly when practicable.

4.4.6 The surfaces of all dry sheets, which require surface finishing, shall be vacuum cleaned before stacking, where there is a risk of airborne asbestos.

4.5 Reclamation of Materials — Reclamation of materials shall be made either by watering to suppress the generated dust while cutting or by dust extraction means.

4.6 Dry Waste Recycling — When dry waste recycling system is employed, asbestos cement dry waste shall be pulverized in an enclosed system with suitable exhaust to avoid escape of dust into atmosphere.

4.7 Asbestos Cement Moulded Goods Manufacturing

4.7.1 In case the moulded goods need manual finishing, the same shall be undertaken when the product is wet by using a rough rasp hand file. Alternatively, the operation shall be done under exhaust hood. Also in the dust extraction system, air shall be downwards to avoid inhalation of generated dust by the worker.

5. GENERAL VENTILATION

5.1 Where appropriate, in conjunction with local exhaust ventilation the entire work area should be supplied with clean air to replace the air as it is exhausted and to reduce airborne asbestos concentrations.

5.2 The flow rates of general ventilation shall be sufficient to change the air of the workplace according to safety and health requirements.

5.3 The exhausted air shall be efficiently filtered and shall not be recirculated back to the working environment.

6. CLEANING OF PLANT AND PREMISES

6.1 The work premises shall be maintained in a clean state and free from asbestos waste. All machinery, plant and equipment together with all external surfaces of exhaust ventilation equipment and all internal sur-

faces of the building shall be kept free from dust. Cleaning shall be done in accordance with the provisions laid down in IS : 11767-1986*.

7. DISPOSAL OF WASTE

7.1 All waste material shall be disposed of in accordance with the provisions laid down in IS : 11768-1986†.

*Recommendations for cleaning of premises and plants using asbestos fibres.

†Recommendations for disposal of asbestos waste material.

(Continued from page 2)

Asbestos Cement Products Subcommittee, BDC 2 : 3

Convener

DR S. K. CHOPRA
S-436 Greater Kailash
New Delhi

Members

SHRI S. K. BANERJEE
SHRI N. G. BASAK

Representing

National Test House, Calcutta
Directorate General of Technical Development,
New Delhi

SHRI P. K. JAIN (Alternate)
SHRI S. N. BASU

Directorate General of Supplies & Disposals,
New Delhi

SHRI T. N. OBOVEJA (Alternate)
SHRI S. R. BHANDARI

Shree Digvijay Cement Co Ltd, Bombay

SHRI V. R. NATARAJAN (Alternate)

SHRI S. K. CHAKRABORTY
Development Commissioner, Small Scale Industries,
New Delhi

SHRI S. C. KUMAR (Alternate)

DEPUTY DIRECTOR STANDARDS (B & S)
Research, Designs & Standards Organization
(Ministry of Railways), Lucknow

ASSISTANT DIRECTOR STANDARDS (B & S)-II (Alternate)

DIRECTOR, ENGINEERING GEOLOGY DIVISION I
Geological Survey of India, Calcutta

SHRI S. K. MATHUR (Alternate)

SHRI S. GANAPATHY
Southern Asbestos Cement Ltd, Madras

GENERAL MANAGER (CEMENT)
Rohtas Industries Ltd, Dalmianagar

SHRI D. N. SINGH (Alternate)

SHRI S. S. GOENKA
Sarbamangala Manufacturing Co, Calcutta

SHRI I. P. GOENKA (Alternate)

SHRI SRINIVASAN N. IYER
Everest Building Products Ltd, Bombay

DR V. G. UPADHYAYA (Alternate)

SHRI P. S. KALANI
Saurabh Construction Co, Indore

DR KALYAN DAS
Central Building Research Institute (CSIR),
Roorkee

SHRI K. D. DHARIYAL (Alternate)

LT-COL KAMLESH PRAKASH
Engineering-in-Chief's Branch, Army Headquarters,
New Delhi

SHRI K. R. BHAMBANI (Alternate)

SHRI HARSHAD R. OZA
Flowel Asbestos Products, Ahmadabad

SHRI V. PATTABHI
Hyderabad Industries Ltd, Hyderabad

SHRI A. K. GUPTA (Alternate)

DR N. RAGHAVENDRA
National Council for Cement and Building
Materials, New Delhi

DR A. V. R. RAO
National Buildings Organization, New Delhi

SHRI J. SEN GUPTA (Alternate)

SUPERINTENDING SURVEYOR OF WORKS (CZ)
Central Public Works Department, New Delhi

SURVEYOR OF WORKS (CZ) (Alternate)

SHRI S. A. SWAMY
Municipal Corporation of Delhi, Delhi

(Continued on page 11)

(Continued from page 10)

Panel for Safety in Handling and Use of Asbestos, BDC 2 : 3/P2

<i>Convener</i>	<i>Representing</i>
SHRI D. K. BISWAS	Department of Bio-Technology (Ministry of Science and Technology), New Delhi
<i>Members</i>	
SHRI B. K. BANERJEE	Sundaram-Abex Ltd, Madras
SHRI K. PANDARINATH (<i>Alternate</i>)	
SHRI N. G. BASAK	Directorate General of Technical Development, New Delhi
SHRI P. K. JAIN (<i>Alternate</i>)	
SHRI S. K. CHAKRABORTY	Development Commissioner, Small Scale Industries, New Delhi
SHRI S. C. KUMAR (<i>Alternate</i>)	
DR G. G. DAYAY	In personal capacity (7/72, Varma Nagar, Old Nagardas Road, Andheri East, Bombay)
DIRECTOR	National Institute of Occupational Health, Ahmadabad
DR S. K. DAVE (<i>Alternate</i>)	
SHRI S. GANAPATHY	Southern Asbestos Cement Ltd, Madras
SHRI S. A. BHIMA RAJA (<i>Alternate</i>)	
DR H. N. GUPTA	Directorate General of Factory Advice Service and Labour Institutes, Bombay
SHRI V. S. SASHIKUMAR (<i>Alternate</i>)	
SHRI SRINIVASAN N. IYER	Everest Building Products Ltd, Bombay
SHRI T. S. PRADHAN (<i>Alternate</i>)	
BRIG D. B. KAPOOR (RETD)	Asbestos Information Centre (India), New Delhi
DR J. L. KAW	Industrial Toxicology Research Centre (CSIR), Lucknow
DR N. K. MEHROTRA (<i>Alternate</i>)	
DR M. V. NANOTHI	National Environmental Engineering Research Institute (CSIR), Nagpur
DR D. M. DHARMADHIKARI (<i>Alternate</i>)	
SHRI G. K. PANDEY	Department of Environment, New Delhi
SHRI V. PATTABHI	Hyderabad Industries Ltd, Hyderabad
DR S. P. VIVEK CHANDRA RAO (<i>Alternate</i>)	
DR N. RAGHAVENDRA	National Council for Cement and Building Materials, New Delhi
SHRI RATTAN LAL (<i>Alternate</i>)	
SHRI S. RAMASWAMY	Hindustan Ferodo Ltd, Bombay
SHRI A. HOMEM (<i>Alternate</i>)	
DR A. V. R. RAO	National Buildings Organization, New Delhi
SHRI D. N. MATHUR (<i>Alternate</i>)	
SHRI B. K. SHARAN	Directorate General of Mines Safety (Ministry of Labour), Dhanbad
DR D. K. SRIVASTAVA (<i>Alternate</i>)	
SHRI NAVNIT TALWAR	Reinz Tal-Broz (Pvt) Ltd, New Delhi
SHRI A. K. SHARMA (<i>Alternate</i>)	

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

Base Units

QUANTITY	UNIT	SYMBOL
Length	metre	m
Mass	kilogram	kg
Time	second	s
Electric current	ampere	A
Thermodynamic temperature	kelvin	K
Luminous intensity	candela	cd
Amount of substance	mole	mol

Supplementary Units

QUANTITY	UNIT	SYMBOL
Plane angle	radian	rad
Solid angle	steradian	sr

Derived Units

QUANTITY	UNIT	SYMBOL	DEFINITION
Force	newton	N	1 N = 1 kg.m/s ²
Energy	joule	J	1 J = 1 N.m
Power	watt	W	1 W = 1 J/s
Flux	weber	Wb	1 Wb = 1 V.s
Flux density	tesla	T	1 T = 1 Wb/m ²
Frequency	hertz	Hz	1 Hz = 1 c/s (s ⁻¹)
Electric conductance	siemens	S	1 S = 1 A/V
Electromotive force	volt	V	1 V = 1 W/A
Pressure, stress	pascal	Pa	1 Pa = 1 N/m ²

AMENDMENT NO. 1 SEPTEMBER 2005
TO
IS 11770(PART 1) :1987 RECOMMENDATIONS
FOR CONTROL OF EMISSION OF ASBESTOS DUST
IN PREMISES MANUFACTURING PRODUCTS
CONTAINING ASBESTOS

PART 1 ASBESTOS CEMENT PRODUCTS

[*Page 5, clause 3.2(f)*] – Substitute the following for the existing:

¹Isolate and provide enclosures for those processes with potential to generate dust levels higher than permissible exposure limit.’

(*Page 7, clause 4.2.6*) — Substitute the following for the existing

‘Empty bags shall be shredded and recycled into the processor disposed off according to the provisions given in IS 11768: 1986.’

(*Page 7, clause 4.3.3*) — Substitute the following for the existing:

‘All storage of asbestos cement products on site shall be within a designated area where there is no possibility of damage by moving objects. The designated area shall be maintained in a clean condition.’

(*Page 8, clause 4.4.6*) — Substitute the following for the existing “All dry sheets that have undergone surface finishing, shall be vacuum cleaned or wet mopped before stacking to avoid risk of airborne asbestos.”

(*Page 8, clause 4.6*) — Substitute the following for the existing:

‘4.6 Recycling of Waste

4.6.1 Dry Waste Recycling

When dry waste recycling system is employed, asbestos cement dry waste shall be pulverized in an enclosed system with suitable exhaust or subjected to ball mill where grinding is done in wet condition to avoid escape of dust into atmosphere.

4.6.2 Green Waste Recycling

Side cuttings of sheets, during manufacture, **shall** be totally recycled into process.

Amend No. 1 to IS 11770(Part 1): 1987

4.6.3 Reuse of Collected Asbestos and Asbestos Cement Dust

Asbestos fibrous dust collected from bag filters and asbestos cement dust collected from pulverizer unit **shall** be recycled into process without **affecting** the quality of product.'

(*Page 9, clause 7.1*) — Substitute the following for the existing:

'Asbestos cement waste shall **be** recycled to the extent possible and the **remaining** waste shall **be** disposed ~~off~~ in accordance with the provisions **laid** down in IS 11768 :1986.'